

## Gloucester

## 703-ST~715-ST

Our Gloucester fixtures are just nice. The pendants look equally as good with chain or stem suspensions. And they blend seamlessly into a variety of sanctuaries and auditoriums. A really unusual feature of these lights is their lack of an upper support frame. Without that frame we are free to project light against unshadowed arches, making a beautiful symmetric glowing surface. The fixture actually propels more light upwards because of it as well. With a variety of metal, acrylic and glass types to choose from, you can easily customize to suit your building's interior.

## ~Gloucester Series~

Chandelier:741-CHT~773-CHT Pendant:701-PT~717-PT

Ceiling Mount:704-CT~717-CT

Wall Mount:701-WT~713-WT

## S-Pendant:703-ST~715-ST

Mounting:Lightsmith fixtures mount to standard 4" octagon electrical boxes unless otherwise specified. All hardware and canopies supplied.

Listing and Warranty: Lightsmith fixtures are Underwriters Laboratories listed and carry a standard three year warranty against defects in materials and labor beginning at date of shipment.













DIFFUSER (Example: BGA-ECH)





Notes~Modifications

|              | Fixture Number | <u>Dimensions</u> | <u>Lamping</u>                 | Weight | Stem/Chain | <u>Options</u>            |
|--------------|----------------|-------------------|--------------------------------|--------|------------|---------------------------|
|              |                | 12w x 18h         | 2-13wCled/1-23wCled            | 14 lbs | 3' Std     | L213,L138                 |
| ш            | 704-ST         | 14w x 18h         | 3-13wCled/1-38wCled            | 17 lbs | 3' Std     | L313,L152                 |
| 뭐            |                |                   |                                |        |            | DALI,REM,FUS**            |
|              | $\Box$         |                   |                                |        |            | , ,                       |
|              |                |                   |                                |        |            |                           |
|              |                |                   |                                |        |            |                           |
|              | ☐ 712-ST       | 12w x 18h         | 3-60wA/1-200wBR40              | 11 lbs | 3' Std     | N300                      |
|              | 714-ST         | 14w x 18h         | 3-100wA/1-250wP38              | 14 lbs |            | N500                      |
| SS           | 714-31         | 14W X 1011        | 3-100WA/1-250WF36              | 14 105 | 3 Siu      | 14300                     |
| Į į          | $  \square  $  |                   |                                |        |            |                           |
| INCANDESCENT |                |                   |                                |        |            |                           |
|              | $\cup$         |                   |                                |        |            |                           |
|              |                |                   |                                |        |            |                           |
| 国            |                | 12w x 18h         | 2-32wCFT/2-32wCFTdn            | 13 lbs | 3' Std     | L213                      |
| 핑            | 715-ST         | 14w x 18h         | 2-42wCFT/2-42wCFTdn            | 16 lbs | 3' Std     | L313                      |
| -LUORESCENT  |                |                   |                                |        |            | DIM,REM,FUS*              |
| 힐            |                |                   |                                |        |            |                           |
|              |                |                   |                                |        |            |                           |
| ,            |                |                   | ~Two Circuits Standard Wiring~ |        |            | *All Fluorescent Fixtures |

|                | ~  | *All Fluorescent Fixtures  **All LED Fixtures   |  |  |
|----------------|--|---|--|--|
| DIFFUSER       | BGA: Beige Alabaster Acrylic NHA: Natural Horn Acrylic WHA: White Alabaster Acrylic HNA: Honey Alabaster Acrylic WOA: White Opal Acrylic                       | GRA: Green  EGA: Earth G  DGA: Deep G  SOG: Streake  WOG: White G   | *Etched option creates a matte, non-glossy finish on one side of the diffuser. (Example:WOA-ECH)   |  |
|                | SOLID BRASS FINISHES PAIN  | TED METAL FINISHES  | ALUMINUM FINISH  | ES STAINLESS STEEL FINISHES  |
| [METAL FINISH] | SBB: Satin Brass PBB: Polished Brass ANB: Antique Nickel SNB: Satin Nickel PNB: Polished Nickel AZB: Antique Bronze SZB: Satin Bronze PZB: Polished Bronze SCF | P: Dark Green P: Verde Green P: Charcoal Gray P: Medium Bronze P: Satin Black P: Dark Bronze P: Light Bronze P: Medium Gold P: Sponged Copper Custom Paint* | SAA: Satin Alur SNA: Satin Nick PAA: Polished Alu BBA: Burnished RNA: Red Naval SGA: Satin Gole SBA: Satin Broo ORA: Oil Rubbed SCA: Satin Cop CSA: Custom Alu | tel DSS: Distressed uminum PSS: Polished Bronze HSS: Hammered bronze Distressed  PSS: Polished HSS: Hammered  Bronze Deer Distressed |
| OPTIONS        | N300: 300wPar56 Downlight N500: 500wPar56 Downlight DiM: Dimming Ballast REM: Remote Emer.Ballast  | L213: 2-13wCLE L313: 3-13wCLE L138: 1-38wCLE L152: 1-52wCLE   | ED Uplight ED Downlight  | FUS: Fusing<br>DALI: Dali dimming LED  |

STEM=S+Lgth

(Example:S-96"

CHAIN=C+Lgth

(Example:C-96"

NR=Not required

**OPTIONS** 

(Example:DIM,REM)



MODIFICATIONS

(Example:Custom Paint\*)

**VOLTAGE** 

(120V)

(277V)

(347V)

METAL FINISH

(Example: ABB)

©2012 Lightsmith